



Declaration of performance

KNAUF Therm Pro Dach/Podłoga EPS 100 λ 36 d_N 260 (TYP EPS 100)

No 08/260/KA/2016.

| | |
|---|--|
| 1. Unique identification code of the product-type: | KNAUF Therm Expert Floor Heating EPS 100 λ 36 d _N 260 (TYP EPS 100) EPS –EN 13163-T(1)-L(2)-W(2)-S(2)-P(5)-BS150-CS(10)100-DS(N)2-DS(70,-)1-DLT(1)5-TR150 |
| 2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specifications, as foreseen by the manufacturer: | Thermal insulation for buildings. |
| 3. Name, registered trade name or registered trade mark and contact address of the manufacturer | Knauf Industries Polska Sp. z o.o. Zakład: Adamowice ul. Styropianowa 1, 96-320 Mszczonów |
| 4. Name and contract address of the authorized representative: | Not relevant |
| 5. System or systems of assessment and verification of constancy of performance of the construction product : | System 3 |
| 6a. Harmonised standard | EN 13163:2012+A1:2015. |
| Notified body: | Instytut Techniki Budowlanej (Polish Building Institute) – No of notification 1488 |
| 6b. European Assessment Document: | Not relevant |
| European Technical Assessment: | Not relevant |
| Technical Assessment Body: | Not relevant |
| Notified Body: | Not relevant |

7. Declared performance :

| Essential characteristics | Performance | Declared class/level/NPD ^{a)} | Harmonised technical specification |
|--|---|--|------------------------------------|
| Thermal resistance | Thermal conductivity and resistance | $R_D \geq 7,00 \text{ m}^2\text{K/W}$ $\lambda_D \leq 0,036 \text{ W/mK}$ | EN 13163:2012+A1:2015 |
| | Thickness [mm] | $T(1) (\pm 1 \text{ mm})$ $d_N - 260 \text{ [mm]}$ | |
| Reaction to fire | Reaction to fire | E | |
| Durability of reaction to fire against heat, weathering, ageing /degradation | Durability characteristics ^{b)} | E | |
| Durability of thermal resistance and thermal conductivity against ageing/degradation | Thermal resistance and thermal conductivity ^{c)} | $R_D \geq 7,00 \text{ m}^2\text{K/W}$ $\lambda_D \leq 0,036 \text{ W/mK}$ | |
| | Durability characteristics | NPD | |
| Compressive strength | Compressive stress at 10% deformation CS (10) [kPa] | CS(10)100 ($\geq 100 \text{ kPa}$) | |
| Tensile/Flexural strength | Bending strength BS [kPa] | BS 150 ($\geq 150 \text{ kPa}$) | |
| | Tensile strength perpendicular to faces TR [kPa] | TR 150 ($\geq 150 \text{ kPa}$) | |
| Durability of compressive strength against ageing and degradation | Compressive creep CC [%] | NPD | |
| | Freeze-thaw resistance [%] | NPD | |
| | Long-term thickness reduction [mm] | NPD | |
| Water permeability | Long term water absorption by immersion WL(T) | NPD | |
| | Long term water absorption by diffusion WD(V) | NPD | |
| Water vapour permeability [μ] | Water vapour transmission [μ] | NPD | |
| Impact noise transmission index (for floors) | Dynamic stiffness SD [MN/m^3] | NPD | |
| | Thickness d_L [mm] | NPD | |
| | Compressibility CP [mm] | NPD | |
| Continuous glowing combustion | Continuous glowing combustion ^{d)} | NPD | |
| Release of dangerous substances to the indoor environment | Release of dangerous substances ^{d)} | NPD | |

^{a)} NPD – No Performance Determined ;

^{b)} The fire performance of EPS does not deteriorate with time ;

^{c)} Thermal conductivity of EPS Products does not change with time ;

^{d)} European test methods are under development ;



Information concerning dangerous substances contained in the Substance Characteristics Sheet.

8. Special technical documentation

Not relevant

The performances of the above identified products are in conformity with the set of declared performances. This declaration of performance is issued in accordance with the EU Construction Products Regulation no 305/2011 under the sole responsibility of the above identified manufacturer.

Signed for and on behalf of the manufacturer by:

[Name and surname]

Wojciech Kossakowski

at [place]

Adamowice

Issued on [date of issue]

01.04.2016

[signature]

A handwritten signature in blue ink, appearing to read 'W. Kossakowski'.